

a fluidized-bed furnace is divided by a partition wall into a gasification furnace and a combustion furnace;

a revolving flow of a fluidized medium in which an intense fluidizing region of the fluidized medium is formed so as to have a substantially high fluidizing velocity in the fluidized-bed in a certain region, thus generating an upward flow of the fluidized medium, and a weak fluidizing region of the fluidized medium is formed so as to have a substantially low fluidizing velocity in the fluidized-bed in another region, thus generating a descending flow of the fluidized medium, is formed in at least one of said gasification furnace and said combustion furnace;

a circulating flow of the fluidized medium is formed between said gasification furnace and said combustion furnace; and

a heat transfer surface is disposed in said combustion furnace.

REMARKS

Kindly enter the above new claims prior to initial examination.

Respectfully submitted,

Shuichi NAGATO et al.

By: *Charles R. Watts*

Charles R. Watts
Registration No. 33,142
Attorney for Applicants

CRW/jmj
Washington, D.C. 20006-1021
Telephone (202) 721-8200
Facsimile (202) 721-8250
June 22, 2001

RECEIVED
JUN 28 2001
TC 1700 MAIL ROOM
THE COMMISSIONER IS AUTHORIZED
TO CHARGE ANY DEFICIENCY IN THE
FEE FOR THIS PAPER TO DEPOSIT
ACCOUNT NO. 23-0975.